



YOU'LL NEVER BE BETTER PROTECTED

## Mobile, Fall Arrest, Man Anchor System



**There is a legal requirement to ensure a safe and efficient maintenance regime for people working at heights. Without a correctly tested and installed system you can be held personally responsible for the safety of your personnel**

- The Kee Anchor® System has been independently tested by Lloyd's British and Apave, both leading independent Test Houses
- Conforms to the requirements of the P.P.E. guideline 89/686/EEC and is tested to conform to NF EN795:1996/Amendment A1: December 2000 (equivalent to pr EN 795:2003 class E), BS 7883 class E and ISO 14567
- The Kee Anchor® system can be used on roofs up to a 5 degree slope
- Multi purpose weights can be used with the KeeGuard roof edge protection system
- Suitable for use on Mineral Felt and Single Ply membrane roof surfaces
- Corrosion resistant for long lasting service
- Easy to assemble
- Suitable for use with lanyard's and Energy Absorption devices conforming to EN354, EN355 and EN 360
- The manufacturer of your chosen lanyard must affirm that it can be used in the horizontal configuration and over the edge of any potential drop



FM 36179



**The Kee Anchor® system is a modular dead weight anchor, for use with Personal Protection Equipment conforming to the latest EU regulations and can be used on mineral felt and single ply membrane – be it wet or dry!**

The Kee Anchor System is designed for use on roofs where there are no permanent guardrails, such as KeeGuard®, or other anchor devices, in order to allow safe freedom of movement around the roof space. The Kee Anchor system offers the solution to the problem of minimal time maintenance operations for those jobs requiring occasional roof access. The system's modular components have been designed for ease of assembly on site and for transporting the system to site.

Another bonus of the Kee Anchor system is that the weights are interchangeable with the KeeGuard® system, thus ensuring safety whilst fitting a KeeGuard® system and ease of disassembly as the weights can be integrated into the KeeGuard® system. For added safety all of the weights that come into contact with the roof are fitted with protective anti-slip rubber pads. The Kee Anchor system offers a low maintenance, reliable and simple to assemble solution to working at heights requiring no drilling, special anchorage or penetration of the roof membrane. All components are zinc coated to ensure long lasting corrosion resistance and the grubscrews used in the system are case hardened and feature Kee Coat® protection. This is combined with the ThreadKoat® (patented) factory applied coating for the threaded recesses.



**The Kee Anchor® modular design takes the complexity and cost out of working at heights - for good!**



Kee Klamp Limited  
1 Boulton Road  
Reading  
RG2 0NH  
United Kingdom  
Tel: +44 (0) 118 931 1022  
Fax: +44 (0) 118 931 1146  
Email: sales@keeanchor.com  
www.keeanchor.com

Whilst every effort has been made to ensure the accuracy of the information contained in this brochure Kee Klamp Ltd cannot be held responsible for any errors or omissions. Kee Klamp Ltd reserve the right to alter or withdraw products without prior notice. Kee Klamp Ltd accept no responsibility for any loss or damage arising from improper use of their products.

Copyright © 2006 Kee Klamp Ltd All Rights Reserved. Kee Anchor is a trade mark of Kee Klamp Ltd.